



- Modular construction design for easy maintenance

- Support second display with adjustable swivel angle
- 20-90° adjustable main display
- Effective Heat Dissipation System
- I/O interface for easy peripherals connection
- Two 2.5" SATA hard disk bays and one CompactFlash card slot for storage
- IP-64 compliant front pane

Model Name EP-7000

[illegible]

CPU **I/O** **GPU**

1GHz to 500MHz @ 100MHz/

1 GHz	10 GHz	20 GHz	30 GHz	40 GHz	50 GHz	60 GHz	70 GHz	80 GHz	90 GHz	100 GHz	110 GHz	120 GHz	130 GHz	140 GHz	150 GHz	160 GHz	170 GHz	180 GHz	190 GHz	200 GHz	210 GHz	220 GHz	230 GHz	240 GHz	250 GHz	260 GHz	270 GHz	280 GHz	290 GHz	300 GHz	310 GHz	320 GHz	330 GHz	340 GHz	350 GHz	360 GHz	370 GHz	380 GHz	390 GHz	400 GHz	410 GHz	420 GHz	430 GHz	440 GHz	450 GHz	460 GHz	470 GHz	480 GHz	490 GHz	500 GHz	510 GHz	520 GHz	530 GHz	540 GHz	550 GHz	560 GHz	570 GHz	580 GHz	590 GHz	600 GHz	610 GHz	620 GHz	630 GHz	640 GHz	650 GHz	660 GHz	670 GHz	680 GHz	690 GHz	700 GHz	710 GHz	720 GHz	730 GHz	740 GHz	750 GHz	760 GHz	770 GHz	780 GHz	790 GHz	800 GHz	810 GHz	820 GHz	830 GHz	840 GHz	850 GHz	860 GHz	870 GHz	880 GHz	890 GHz	900 GHz	910 GHz	920 GHz	930 GHz	940 GHz	950 GHz	960 GHz	970 GHz	980 GHz	990 GHz	1000 GHz
-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	----------

1MByte @ 66MHz Celeron® M

1GHz Intel® Core™2 Duo Processor

M 2014-01-17 14:13:13

MI 2012-01-10 10:10:10

N270	1.6GHz
------	--------

7 x USB 2.0

7 x USD2.0	
4 x USD3.0	4 x USD3.0

4 x RS-232 COM port with LED Indicator

2 x 12V/24V RJ-11 for cash drawer

1 x DB 25	
-----------	--

1 x DB-25	

1 x LAN Port	
--------------	--

1 x 802.11 a/b/g wireless LAN

1 x 502.11 a/b/g wireless LAN	1 x VGA port
-------------------------------	--------------

1 x Power Switch	1 x VGA port
------------------	--------------

7 x USB2.0

1	x	RS-232 COM port with LED Indicator
---	---	------------------------------------

2 1.8V/3.1V BATT. indicator

2 x 12V/24V RJ-11 for cash drawer

1 x DB-25

1 x LAN Port	
--------------	--

Port	Protocol	Service
1	TCP	22 (SSH)
2	TCP	23 (Telnet)
3	TCP	25 (SMTP)
4	TCP	53 (DNS)
5	TCP	80 (HTTP)
6	TCP	110 (POP3)
7	TCP	143 (IMAP)
8	TCP	179 (BGP)
9	TCP	21 (FTP)
10	TCP	22 (SSH)
11	TCP	23 (Telnet)
12	TCP	25 (SMTP)
13	TCP	53 (DNS)
14	TCP	80 (HTTP)
15	TCP	110 (POP3)
16	TCP	143 (IMAP)
17	TCP	179 (BGP)
18	TCP	21 (FTP)
19	TCP	22 (SSH)
20	TCP	23 (Telnet)
21	TCP	25 (SMTP)
22	TCP	53 (DNS)
23	TCP	80 (HTTP)
24	TCP	110 (POP3)
25	TCP	143 (IMAP)
26	TCP	179 (BGP)
27	TCP	21 (FTP)
28	TCP	22 (SSH)
29	TCP	23 (Telnet)
30	TCP	25 (SMTP)
31	TCP	53 (DNS)
32	TCP	80 (HTTP)
33	TCP	110 (POP3)
34	TCP	143 (IMAP)
35	TCP	179 (BGP)
36	TCP	21 (FTP)
37	TCP	22 (SSH)
38	TCP	23 (Telnet)
39	TCP	25 (SMTP)
40	TCP	53 (DNS)
41	TCP	80 (HTTP)
42	TCP	110 (POP3)
43	TCP	143 (IMAP)
44	TCP	179 (BGP)
45	TCP	21 (FTP)
46	TCP	22 (SSH)
47	TCP	23 (Telnet)
48	TCP	25 (SMTP)
49	TCP	53 (DNS)
50	TCP	80 (HTTP)
51	TCP	110 (POP3)
52	TCP	143 (IMAP)
53	TCP	179 (BGP)
54	TCP	21 (FTP)
55	TCP	22 (SSH)
56	TCP	23 (Telnet)
57	TCP	25 (SMTP)
58	TCP	53 (DNS)
59	TCP	80 (HTTP)
60	TCP	110 (POP3)
61	TCP	143 (IMAP)
62	TCP	179 (BGP)
63	TCP	21 (FTP)
64	TCP	22 (SSH)
65	TCP	23 (Telnet)
66	TCP	25 (SMTP)
67	TCP	53 (DNS)
68	TCP	80 (HTTP)
69	TCP	110 (POP3)
70	TCP	143 (IMAP)
71	TCP	179 (BGP)
72	TCP	21 (FTP)
73	TCP	22 (SSH)
74	TCP	23 (Telnet)
75	TCP	25 (SMTP)
76	TCP	53 (DNS)
77	TCP	80 (HTTP)
78	TCP	110 (POP3)
79	TCP	143 (IMAP)
80	TCP	179 (BGP)
81	TCP	21 (FTP)
82	TCP	22 (SSH)
83	TCP	23 (Telnet)
84	TCP	25 (SMTP)
85	TCP	53 (DNS)
86	TCP	80 (HTTP)
87	TCP	110 (POP3)
88	TCP	143 (IMAP)
89	TCP	179 (BGP)
90	TCP	21 (FTP)
91	TCP	22 (SSH)
92	TCP	23 (Telnet)
93	TCP	25 (SMTP)
94	TCP	53 (DNS)
95	TCP	80 (HTTP)
96	TCP	110 (POP3)
97	TCP	143 (IMAP)
98	TCP	179 (BGP)
99	TCP	21 (FTP)
100	TCP	22 (SSH)
101	TCP	23 (Telnet)
102	TCP	25 (SMTP)
103	TCP	53 (DNS)
104	TCP	80 (HTTP)
105	TCP	110 (POP3)
106	TCP	143 (IMAP)
107	TCP	179 (BGP)
108	TCP	21 (FTP)
109	TCP	22 (SSH)
110	TCP	23 (Telnet)
111	TCP	25 (SMTP)
112	TCP	53 (DNS)
113	TCP	80 (HTTP)
114	TCP	110 (POP3)
115	TCP	143 (IMAP)
116	TCP	179 (BGP)
117	TCP	21 (FTP)
118	TCP	22 (SSH)
119	TCP	23 (Telnet)
120	TCP	25 (SMTP)
121	TCP	53 (DNS)
122	TCP	80 (HTTP)
123	TCP	110 (POP3)
12		

2 x 12V/24V RJ-11 for cash drawer
1 x DB-25
1 x LAN Port
1 x 802.11 a/b/g wireless LAN
1 x Power Switch
7 x USB2.0
4 x RS-232 COM port with LED Indicator
1 x 12V/24V RJ-11 for cash drawer
1 x DB-25
1 x LAN Port
1 x Power Switch

Memory	Built-in 1GB DDR2 memory, supports 2 x 240 pin dual channel DDR2 400/533MHz
Max Resolution	1024 x 768
Brightness (cd/m²)	350/350/250/250/250
Contrast Ratio	400/400/600/600/600:1
LCD Color	262K/262K/6.7M/6.7M/6.7M
Touch Screen Type	Resistive Type 5-Wire
Pixel Pitch (mm)	0.297(H) x 0.297(V)
Viewing Angle (H-V)	120/120/160/160/160
Backlight MTBF	50000/50000/50000/50000 hours
IP Level	IP64 (front panel)
Front Panel Color	Black
HDD	2 x 2.5" SATA HDD Bay
SSD	1 x CF Type II slot
Power Consumption	66W
EMC and Safety	CE/ FCC/ CB/ UL
Operating Temperature	0°C~40°C
Dimension (WxHxD) (mm)	373 x 390 x 335
Net Weight	8.30 Kg

Ordering Information

Part No.	Description
EP-265-910-10G/WT-R/1GB	15" 350cd/m² XGA POS PC with Intel® Celeron® M 1.0GHz 512K cache CPU, 1GB DDR2
EP-265-GM45-C575/WT-R/1GB	15" 350cd/m² XGA POS PC with Intel® Celeron® 2.0GHz 1MB cache CPU, 1GB DDR2
EP-265E-910-10G/T-R/1GB	15" 250cd/m² XGA POS PC with Intel® Celeron® M 1.0GHz 512K cache CPU, 1GB DDR2
EP-265E-GM45-C575/WT-R/1GB	15" 250cd/m² XGA POS PC with Intel® Celeron® 2.0GHz 1MB cache CPU, 1GB DDR2
EP-265E-N270/T-R/1GB	15" 250cd/m² XGA POS PC with Intel® Atom™ N270 1.6GHz, 1GB DDR2

